

FIBER OPTIC SPLICE CLOSURE-DOME TYPE C



4 branch ports for Φ 14~20mm cable.
12 branch ports for Φ 8~16mm cable.
1 port for Φ 10~25mm uncut cable.

7 branch ports for Φ 8~17.5mm cable.
2 branch ports for different types of drop cable.
1 port for Φ 10~22mm uncut cable.



Mechanical seal for the box, and the optional mechanical seal or heat shrink seal for the cable ports.



Various types of splice trays as options.



Description

- 4 branch ports for Φ 14~20mm cable.
12 branch ports for Φ 8~16mm cable.
1 port for Φ 10~25mm uncut cable.
- Bundle cable capacity: 12-360F, could be installed with 12 trays. With max capacity 12F for each one or 24 trays, with max capacity 6F for each.
- Splice tray could be replaced with splitter tray, each tray could be installed with 2×1:4 and 1×1:8 micro type splitter.
- Protection grade: IP68
- Installed method: Aerial, wall mounting, direct burial, etc.
- Mechanical seal for the box, and the heat shrink seal for cable ports. Good sealing performance.
- Many different types of splice trays as options.
- Size: 625* Φ 270mm
- Weight: 9.5-12kg
- Inner carton size: 775*315*285mm (1 pcs)